

GLADIATOR

SPEAKER NUMBER WAY <i>Crossover</i>	5 way - Possibility for Biwiring or BiAmp 0-50Hz/50Hz-150Hz/150Hz-600Hz/600Hz-20KHz/14KHz- 30KHz
FREQUENCY RESPONSE	15Hz to 30KHz
SENSITIVITY	96 dB
IMPEDANCE	4 ohms - almost resistive up to 600 Hz
POSSIBILITY LINEARZE ON SELECTOR TO SWITCH	YES
WOOFER NORMAL ATTENUATED	YES
MID-WOOFER - 3 POSITIONS: Direct Atten. Min, Atten. Max	YES
MIDTWEETER 3 POSITIONS: Direct Atten. Min, Atten. Max	YES
SUPER-TWEETER. ACTIVATED OR DEACTIVATED	YES
SUB-WOOFER	1 Woofer 42cm - 16,5"
WOOFER - NORMAL/ATTENUATED	1 Woofer 38cm - 15,0"
MID LOW FREQUENCY TRANSDUCER	4 Mid-Woofer 17,5cm - 6,7"
MID-RANGE TWEETERS TRANSDUCER	4 Mid-Tweeter Planar, h20cm
SUPER TWEETERS TRANSDUCER	1 Super Tweeter Ribbon a nastro
DIMENSIONS	Height 78,7" 200cm Width 26,4" 67cm Depth 40,2" 102cm
WEIGHT	250kg (551 lbs)
FINISH STANDARD / CUSTOM	Dark blue elettric metal Red cherry Custom color